



Southeastern Performance Minerals, LLC

SMica 30 Muscovite Mica


General Description

SMica 30 is a wet ground muscovite mica, processed specifically for industrial applications. Proprietary milling induces a high degree of delamination, which translates into a high aspect ratio and increased resiliency. These characteristics make SMica 30 an acceptable, cost effective additive for the following markets:

Roof Coatings	Plastisols
Adhesives	Plastics
Gaskets	Paints & Coatings
Wire & Cable	

Typical Properties

Sieve Analysis	% retained
+100 mesh	trace
+325 mesh	0-6%
Bulk Density (Colgate)	8-14
Mean Particle Size (µm)	30-38
Color, L* value	>90
Moisture Loss @ 100°C	<0.5%
Specific Gravity	2.82
pH	6.0-7.5
CAS No.	12001-26-2



See SDS for safety and regulatory information.

Southeastern Performance Minerals, LLC
 1132 Veal Rd.
 Sandersville, GA 31082

Phone: (478)553-0048
 Fax: (478)553-0050
info@sepm.us

The statements herein are based on data which is believed to be reliable. This data is offered in good faith and typical of normal production. SEPM make no warranty or representation, expressed or implied, regarding the accuracy of this data or the use of this product. The user is solely responsible for the use of this product.

Issue date: 6/11/15

Revised date: 6/18/18