



Product Name: SUPER SEATONE Diarylide Yellow AAOT
Code Number: 11B240
Vehicle Type: Surfactant Blend
Solvent: Water
Color Index Name: Y-14
Suggested for Industrial Finishes ? Selected Applications

Product Line Description: Aqueous pigment dispersions for in-plant tinting of Industrial and Architectural Coatings

Super Seatone® aqueous dispersions are designed to be easy to use, free flowing, viscosity stable pigment concentrates. They are tightly controlled for consistent color characteristics when added by weight.

TYPICAL PROPERTIES

Lbs/gal	9.1
Wt % Pigment	28.4
Vol % Pigment	23.7
Wt % Vehicle Solids	12.9
Vol % Vehicle Solids	15.5
Wt % Volatile	58.7
Vol % Volatile	60.8
VOC g/l *	49
VOC lb/gal *	0.4

CHEMICAL RESISTANCE

(1= Poor, 5 = Excellent)

Aliphatic	5
Aromatic	3
Ketone	5
Ethyl Acetate	3
Ethyl Alcohol	5
Cellosolve	5
DB Phthalate	5
Glycol	4
Dilute Acid	5
Dilute Alkali	4
Soap	5

EXTERIOR DURABILITY

(1= Poor, 5 = Excellent)

MASSTONE	3
TINT	1

HEAT RESISTANCE

(1= Poor, 5 = Excellent)

150 C - 15'	4
150 C - 30'	3

* Note - For aqueous products, VOC is calculated minus water.

DyStar Hilton Davis
 2235 Langdon Farm Rd.
 Chininnati, OH 45237
 USA
 Telephone +1 800-477-1022
 Fax (marketing) +1 513 441 3771
 DyStar-USA@DyStar.com
 www.DyStar.com

This information and our technical advice - whether verbal, in writing or by way of trials - are given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to check its validity and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with our General Conditions of Sale and Delivery.