

ADDITOL[®] XL 121

TYPE

Silicone type paint additive

FORM OF DELIVERY (f.o.d.)

Active substance

approx. 14 %

PRODUCT DATA

Determined per batch:

Non-Volatile Matter DIN EN ISO 3251 non-volatile matter (1 h; 125 °C; 2 g)	[%]	11,5 - 13,5
Iodine Colour Number DIN 6162 iodine colour number		max. 1
Refractive Index DIN 53491 refractive index (20 °C)		1,4850 - 1,4950

Not continually determined:

Colour / Appearance VLN 250 colour		colourless
---------------------------------------	--	------------

Density (Liquids) DIN EN ISO 2811-2 density approx. (20 °C)	[g/cm ³]	0,89
--	----------------------	------

Flash Point DIN EN ISO 1523 flash point approx.	[°C]	5
---	------	---

Appearance
low-viscous liquid

SPECIAL PROPERTIES

Paint additive to enhance mar resistance and levelling of air drying and stoving paints, particularly for silicone modified air drying and stoving alkyd resins.

SUGGESTED USES

Additol XL 121 is a silicone containing paint additive supplied as low-viscous solution. Additol XL 121 enhances mar resistance of solvent-borne paints by reducing the surface resistance of the paint film. Additol XL 121 improves levelling and prevents film structures and thus enhances film performance in general.

Additol XL 121 is suited for air drying alkyds, stoving alkyds, thermosetting acrylic resins, nitrocellulose paints, acid curing paints, alkyd-acrylate-isocyanate systems, and particularly for air drying and stoving-silicone modified alkyd resins. The effect of Additol XL 121 depends on the type of paint system and on the formulation. The quantity of Additol XL 121 may range from 0.1 - 0.5 % on paint as a guide.

PROCESSING

For optimum distribution, Additol XL 121 is added prior to final adjustment of the viscosity and the colour shade.

STORAGE

At temperatures up to 25 °C storage stability packed in original containers amounts to at least 730 days.

DISTINGUISHING FEATURES

In difference to Additol XL 122, Additol XL 121 shows better overspray acceptance.

6.0/30.03.2017 (replaces 5.0/17.09.2013)

• Worldwide Contact Info: www.allnex.com •

Disclaimer: allnex Group companies ("allnex") decline any liability with respect to the use made by anyone of the information contained herein. The information contained herein represents allnex's best knowledge thereon without constituting any express or implied guarantee or warranty of any kind (including, but not limited to, regarding the accuracy, the completeness or relevance of the data set out herein). Nothing contained herein shall be construed as conferring any license or right under any patent or other intellectual property rights of allnex or of any third party. The information relating to the products is given for information purposes only. No guarantee or warranty is provided that the product and/or information is adapted for any specific use, performance or result and that product and/or information do not infringe any allnex and/or third party intellectual property rights. The user should perform its own tests to determine the suitability for a particular purpose. The final choice of use of a product and/or information as well as the investigation of any possible violation of intellectual property rights of allnex and/or third parties remains the sole responsibility of the user.

© 2013 Allnex Belgium SA. All Rights Reserved

Notice: Trademarks indicated with the ®, ™ or * are registered, unregistered or pending trademarks of Allnex Belgium SA or its directly or indirectly affiliated Allnex Group companies.