



PRODUCT CODE **DC55AS(#)**

DRUMSAVER™ DUST CAP

PRODUCT DESCRIPTION: Made from FDA-approved low-density polyethylene anti-stat film, the DC55AS(#) dust caps have a nylon elasticized band that is securely sewn for easy slip on/slip off inspection of the contents of open-head 55-gallon drums.

Cap Specifications

MATERIAL USED

Low-density polyethylene

INSERT DIMENSIONS

Diameter: 19.25"-23.25"

Lay-flat: 34"

Elastic size: 0.5" (+/-0.125")

Average thickness: 4 mil (+/-10%)

WEIGHT

2 oz. (+/-10%)

COVER DESIGN

"Shower cap"

TEMPERATURE PARAMETERS

High (momentary): 175° (195°)F

Low: -40° F

ANTI-STAT

Standard: NFPA-99

Resistivity rating: 10¹¹ Ω/sq. typical

Packaging Specifications

CARTON WEIGHT

15 lb.

CARTON DIMENSIONS

Length: 20.125"

Width: 20.125"

Height: 10"

QUANTITY/CASE

100

PACKAGING STYLE

Nested

CDF's ANTI-STAT LINERS CONTAIN AN INTERNAL ANTI-STAT AGENT THAT IS INTENDED AS AN AID TO REDUCTION OF STATIC BUILD-UP. THEY ARE NOT DESIGNED AS, AND SHOULD NOT BE USED AS, THE PRIMARY CONTROLLER OF STATIC ELECTRICITY IN A PROCESS. CDF'S ANTI-STAT LINERS SHOULD NOT BE USED IN ELECTRO-STATIC COATING SYSTEMS OR OTHER HIGHLY VOLATILE AREAS. PLEASE CONSULT YOUR SAFETY ENGINEER, SAFETY CONSULTANT, OR CDF IF THERE IS ANY QUESTION AS TO APPROPRIATENESS OF USE.

TYPICAL APPLICATIONS: Clear, snug-fitting dust caps shield stored materials from dirt, dust, moisture, insects and other contaminants. The anti-stat additive in the DC55AS(#) helps to reduce static build-up in static sensitive applications compatible with low-density polyethylene such as paints, volatile materials and fine powders.

CDF warrants that its products will be free from defects in material and workmanship for one-hundred eighty (180) days after the date of delivery. Warranty claims must be made in writing no later than five (5) business days after the expiration of the warranty period. CDF's obligations under this warranty are limited solely to replacement of such products as are proven to be defective after CDF's inspection. **Prior to use, the user shall independently determine the suitability of the products for the user's intended use and user assumes all risk and liability whatsoever in connection therewith.** CDF EXPRESSLY DISCLAIMS AND EXCLUDES ANY AND ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE RELATING TO THE USE OR PERFORMANCE OF CDF PRODUCTS. CDF SHALL NOT BE LIABLE FOR PERSONAL INJURY OR PROPERTY DAMAGE UNLESS CAUSED SOLELY BY CDF'S NEGLIGENCE. CDF SHALL NOT BE LIABLE FOR LOSS OF PROFIT OR OTHER SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF THE USE OF CDF PRODUCTS, REGARDLESS OF THE LEGAL THEORY ON WHICH THE CLAIM IS BASED AND EVEN IF CDF HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

**CDF CORPORATION • 77 Industrial Park Road • Plymouth, MA 02360
(800) 443-1920 • fax (508) 747-6333 • www.cdf1.com**

Specifications subject to change without notice.
Product Specification: DC55AS(#)
Revision: G
2.9.11