

ENCOR[®] 413

Acrylic Emulsion Polymer

Product Benefits

ENCOR[®] 413 latex is an acrylic emulsion polymer specifically developed for use in the polymer modification of portland cement and other hydraulic cement compositions. Cementitious products modified with ENCOR[®] 413 latex show improved bond strength to a variety of substrates, including concrete and masonry, wood, and insulating foams. In addition, ENCOR[®] 413 latex improves the flexural and tensile strengths of hydraulic cement concretes. This multicomponent acrylic polymer resists saponification and demonstrates good exterior durability with resistance to UV light and moisture.

Polymer Design

- Acrylic

Performance Benefits

- Improved bond strength
- Good exterior durability
- Resistant to UV light and moisture

Typical Polymer Properties¹

Appearance	White, milky liquid
Total Solids, % by weight	46–48
pH Value	9.0-9.5
Viscosity, LVT #3, 60 rpm, cp	50
Weight per Gallon, 20 °C, lb	8.8
Freeze-Thaw Stability	Good
Minimum Filming Temperature, 50% R.H., °C	13

¹The data provided for these properties are typical values, intended only as guides, and should not be construed as sales specifications.



**Product
Safety**

Before handling the materials listed in this bulletin, read and understand the product MSDS (Material Safety Data Sheet) for additional information on personal protective equipment and for safety, health and environmental information. For environmental, safety and toxicological information, contact our Customer Service Department at 1-866-837-5532 to find an MSDS, or visit our web site: www.arkemacoatingresins.com

No chemical should be used as or in a food, drug, medical device, or cosmetic, or in a product or process in which it may contact a food, drug, medical device, or cosmetic until the user has determined the suitability and legality of the use. Since government regulations and use conditions are subject to change, it is the user's responsibility to determine that this information is appropriate and suitable under current, applicable laws and regulations.

Arkema Coating Resins requests that the customer read, understand, and comply with the information contained in this publication and the current MSDS(s). The customer should furnish the information in this publication to its employees, contractors, and customers, or any other users of the product(s), and request that they do the same.

**Storage and
Handling**

Follow procedures typically recommended for polymer dispersions. Use corrosion-resistant storage tanks and piping. Air-operated diaphragm pumps are preferred. Avoid temperature extremes. Do not freeze; store between 4-40°C.



Arkema Coating Resins
410 Gregson Dr.
Cary, NC 27511

Telephone:
1.800.777.8227

Visit our website:
www.arkemacoatingresins.com

IMPORTANT: The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN.** The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.

© 2012 Arkema Inc. All rights reserved. 10/12
ENCOR® is a registered trademark of Arkema Inc.



is a registered trademark of the American Chemistry Council Inc.