

FOAM BLAST[®] 331

Product Type	Industrial Foam Control Agent										
Product Description	<p>FOAM BLAST 331 is an efficient and effective foam control agent consisting of highly refined mineral oils, inorganic and organic particulate designed specifically for use in the paint industry. FOAM BLAST 331 is easy to incorporate into most paint media. Tests indicate this product to be effective in a wide range of paint and coating applications.</p> <p>FOAM BLAST 331 is composed of ingredients that meet the current requirements of the FDA for food contact applications when used in accordance with the requirements and limitations of 21 CFR: 175.105, 175.300, 176.170, 176.180, 176.200, 176.210, and 178.3120.</p>										
Typical Properties	<table border="1"><tr><td>Appearance</td><td>Opaque tan liquid</td></tr><tr><td>Viscosity (mPa-s) @ 25°C</td><td>1500</td></tr><tr><td>Density (kg/L) @ 25°C</td><td>0.888</td></tr><tr><td>Water Solubility (%)</td><td>< 0.1</td></tr><tr><td>Flash Point (°C) (PMCC)</td><td>180</td></tr></table>	Appearance	Opaque tan liquid	Viscosity (mPa-s) @ 25°C	1500	Density (kg/L) @ 25°C	0.888	Water Solubility (%)	< 0.1	Flash Point (°C) (PMCC)	180
Appearance	Opaque tan liquid										
Viscosity (mPa-s) @ 25°C	1500										
Density (kg/L) @ 25°C	0.888										
Water Solubility (%)	< 0.1										
Flash Point (°C) (PMCC)	180										
Typical Applications	<ul style="list-style-type: none">• Architectural or Industrial Paints and Coatings• Acrylic and latex emulsion polymerization• Adhesives and glues• Water based gravure inks• Wastewater applications										
Addition Levels	<p>FOAM BLAST 331 should be used neat in most applications. The product can normally be added to most systems at a dosage level of 0.1 to 0.25% by weight.</p> <p>In paints, FOAM BLAST 331 should be added to the grind phase at 2-5 lb per 100 gal when used in most formulas. It can be added to the letdown for additional foam control.</p> <p>In many specialty coating applications, FOAM BLAST 331 should be used neat. The product can normally be added to most systems at an addition level of 0.15 to 0.25%.</p>										
Responsible Care	<p>For complete safety, health, personnel protection and first aid information, refer to the Material Safety Data Sheet (MSDS), which can be ordered by calling one of the phone numbers below.</p>										

Updated: March 1, 2013

Emerald Performance Materials , LLC
8309 Wilkinson Blvd
Charlotte, NC 21214
Toll free for placing orders: 1-877-300-9545

Emerald Performance Materials, Corporate
2020 Front Street, Suite 100
Cuyahoga Falls, OH 44221
330.916.6700

Toll Free Technical Assistance: 1-866-688-FOAM

EFCTechnicalService@EmeraldMaterials.com