

LN-PT-0902 Version: A1 Date: Jan 08

LONGSORB 27

SPECIFICATION ITEM

Molecular Weight: 357.9

Slightly yellow powder **Appearance:**

Approx. 1.26 @ 20 °C **Specific gravity:**

0.5 % Max. **Volatility:**

97 % Min. 460 nm **Transmittance:** 98 % Min (10 g in 100 ml toluene: 1 cm cell) 500 nm

98.0 % Min. Assay:

Packing: 25 KGS / DRUM,

125KGS / PALLET

LONGSORB 27 is mainly used as UV absorber for **Application:**

> styrene polymers PVC, unsaturated polyesters, PU, acrylic polymers, polycarbonate adhesives and

> > Tel: 886-2-27718177

Fax: 886-2-27788748

coating.

Notice: Above information is based on our own investigation and experience, we do not assume any responsibility for the performance or result obtained through the use of our product. The users need to check the quality, safety and all properties in their side before they use and commercialize their products. Neither Longchem nor our agents shall take any responsibilities for any injury, loss or damages directly or indirectly caused by our products.

Longchem C & S International Corp.

12FL, 80, Fu Hsing N. Road Taipei, Taiwan, R.O.C.

P.O. Box. 34-167 Taipei, Taiwan