

QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219 QUAKERTOWN, PENNSYLVANIA 18951-0219 (215) 536-3520 FAX (215) 536-6464 www.quakercolor.com

Technical Data Sheet-Leather Finishing Products

Product Code: PR-1238

DESCRIPTION

PR-1238 is a soft, NMP free, high performance, aliphatic polyether polyurethane dispersion.

APPLICATIONS

 Embossable leather base coats, Intermediate coats and some leather topcoat applications where extreme flexibility is required.

FEATURES

- Excellent bally flex properties
- Excellent cold flex properties
- Exceptional hydrolysis resistance
- Improves softness and adhesion of basecoats

PROPERTIES

Percent Solids, weight	32
Specific Gravity, 25°C	1.02
pH, typical value	8.2
Viscosity, cPs	45

STORAGE

Store in a cool, dry place, preferably less than 80°F, to ensure a useful shelf life of eighteen months. Protect from freezing.

Quaker Color manufactures all its products under carefully controlled conditions to meet rigid specifications. The values given in this publication are typical values intended as guidelines for the use of the products, they are not specifications. It is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Should you require the actual specifications currently enforced on specific products contact your Quaker Color representative for the appropriate information.