



PHOTOMER[®] 5444

Polyester Acrylate

Product Data Sheet

General Information

PHOTOMER[®] 5444 is modified polyester acrylate that exhibit good flexibility.

Specification

Appearance	Visual	Clear Liquid
Viscosity @ 25 °C	Brookfield, ISO 2555	20 000 – 40 000 mPa.s
Colour (Gardner)	ISO 4630	≤ 4 Gardner
Acid Value	ISO 660	≤ 10 mg KOH/g

Application

PHOTOMER[®] 5444 is recommended for the graphic arts and wood industry.

Formulated product properties will depend on the actual reactive monomers, oligomers and additives utilized.

Storage & Handling

Storage must be in a cool, shaded, well ventilated and dry area away from direct sources of heat and sunlight. Subject to appropriate storage, our products are durable for at least 6 months.

PHOTOMER[®] 5444 should be handled in accordance with good industrial practice. Further information is provided in the material safety data sheet which is available on request.

Regulatory Status

TSCA (USA), NLP (Europe), IECSC (China), NDSL (Canada), ENCS (Japa), ECL (Korea), TCSI (Taiwan)

Packaging

PHOTOMER[®] 5444 is available in 200 kg steel drums

Disclaimer

The information presented in this data sheet is given in good faith and is based on the material available to us at the time of writing. The information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission or recommendation to practice any patented invention without a license. It is offered solely for consideration, investigation and verification.