TECHNICAL DATA SHEET

YIPIN[®] Iron Oxide Pigment Iron Oxide Yellow S920



| Edition of | 2015-02-18 | | |
|--------------------|----------------------------------|--|--|
| Туре | Yellow pigment | | |
| Delivery Form | Powder | | |
| Chemical Class | Synthetic iron oxide alpha-FeOOH | | |
| Color Index | Pigment yellow 42(77492) | | |
| CAS No. | 20344-49-4 | | |
| Use Recommendation | Coating、Construction、Plastic | | |

COLOR VALUES AND TINTING STRENGTH

| Reference | | | Standard: ASTM |
|-------------------------------|------------|-------|----------------|
| | <u>Min</u> | Max | Test Method |
| Binder | Test Paste | Based | |
| Dildei | On R-05 | | |
| Full Shade | | | ASTM D 387 |
| $\triangle L^*$ | -0.6 | +0.6 | |
| $	riangle \mathbf{a^*}$ | -0.6 | +0.6 | |
| $	riangle \mathtt{b}^{\star}$ | -0.6 | +0.6 | |
| ∆E*ab | | 0.8 | |

TECHNICAL DATA

| | <u>Min</u> | <u>Max</u> | Test Method |
|--|------------|------------|----------------------|
| Water-Soluble Content [%] | | 0.5 | ASTM D 1208 |
| Sieve Residue (0.045mm) [%] | | 0.1 | ASTM D 185 |
| Fe ₂ O ₃ [%] | 86.0 | | ASTM D 50 |
| Moisture (After Production) [%] | | 1.0 | ASTM D 280 |
| Loss on Heating 1000°C ^{1/2} h [%] | | 14.0 | ASTM D1208 |
| Particle Shape | acicular | | Electron Micrographs |

 YIPIN PIGMENTS, INC.
 Tel:+1-909-243-7394
 Fax: +1-909-243-7397
 www.

 一品颜料
 Tel:+86-21-5950 8509
 Fax: +86-21-5950 7893
 wh@g

TECHNICAL DATA SHEET

YIPIN[®] Iron Oxide Pigment Iron Oxide Yellow S920



| | <u>Approx.</u> | |
|--------------------------------|----------------|----------------------|
| Predominant Particle size [µM] | 0.1×0.8 | Electron Micrographs |
| Oil Absorption [g/100g] | \sim 35 | ASTM D 281 |
| Density [g/ml] | \sim 4.0 | ASTM D153 |
| | | |

STANDARD PACKAGING

20kg/bag, 50LB/bag

TRANSPORT AND STORAGE

Protect against weathering. Store in a dry place and avoid extreme fluctuations in temperature. Special conditions for opened packaging: Close bags after use to prevent the absorption of moisture and contamination.

SAFETY

The product is not classified as dangerous under the relevant EC directives and corresponding national regulations valid in the individual EU member states. It is not dangerous according to transport regulations. In countries outside the EU, compliance with the respective national legislation concerning the classification, packaging, labeling and transport of dangerous substances must be ensured.

The information contained in the safety data sheet should be observed.

This contains information on handing, product safety and ecology.

This information is given in good faith, without warranty. It is also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General conditions of sale and delivery.