

QUAKER COLOR

DIVISION OF McADOO & ALLEN, INC.

201 S. HELLERTOWN AVENUE P.O. BOX 219 QUAKERTOWN, PENNSYLVANIA 18951-0219 (215) 536-3520 FAX (215) 536-6464 www.quakercolor.com

PRODUCT LITERATURE

ST-844 DULL SOFT FEEL RESIN

ST-844 is a unique **Solvent Free**, inherently dull, lightfast polyurethane resin with exceptional physical properties in terms of abrasion resistance, flexibility, and water resistance.

ST-844 can be used in base coat or topcoat formulations to produce low gloss coatings with exceptional physical properties and **Soft Touch** hand feel aesthetics. Based on the inherently dull characteristics of **ST-844** low gloss coatings can be produced without the need for external dulling agents. By reducing or eliminating the need for external dulling agents the coatings physical properties and surface feel is enhanced.

ST-844 is compatible with most acrylic and polyurethane resins, and can be crosslinked with **XL-36 X-Linker** to enhance performance.

Automotive topcoats prepared with **ST-844** exhibit, excellent flow, and surface feel properties and wet crock resistance.

Typical Properties:

Total Solids: 35 %

Density: 1.04 g/cm³

Viscosity: 300 cps

pH: 8.6

Film Properties:

Tensile Strength: 4000 psi

Elongation: 900 %

Modulus at 100% Elong: 450 psi